



BEHR PREMIUM™ Chalk Decorative Aerosol

- Indoor/Outdoor Use
- Corrosion Resistant
- Excellent Adhesion

70244C	Miniature Rose	74744C	Morocco Red
70844C	Tin White	74944C	Rustic Taupe
71044C	Pale Moon	75044C	Linen White
72844C	Surf	75144C	Chiffon Cream
73544C	Gingham	75244C	Aged Gray
73844C	Timeless Blue	75644C	Black Evergreen
74544C	Classic Noir	714044C	Matte Clear



Protect
from Freezing



15-30 minutes
Dry to Touch
<1 Hr. or greater
than 24 Recoat time



1.5-2 m²
(15-20 sq ft)
Coverage



Mineral Spirits
Clean-Up

BEHR PREMIUM™ Chalk Decorative Aerosol is an easy way to create a unique and trendy look for your next paint project. This simple two-step paint and wax process allows your personal style and vision to come to life, whether you're looking for an aged antique look or prefer more of a vintage modern flair. The wide variety of BEHR paint colours and BEHR PREMIUM™ Decorative Waxes make every application completely tailored to achieve the one-of-a-kind look you desire. BEHR PREMIUM™ Chalk Decorative Aerosol can be applied over most existing surfaces with very little surface preparation and delivers a smooth matte finish. Perfect for refreshing old and new wooden furniture, cast stone, concrete, and even metal surfaces to create one-of-a-kind accent pieces.

†A primer coat may be needed on some surfaces.

PREPARATION

The surface must be clean, free of dust, grease, wax, peeling paint, mold or mildew. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

†**Peeling or Checked Paint:** Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

***Glossy Surfaces:** For maximum adhesion, scuff sand the surface thoroughly before painting.

APPLICATION

Eye protection is recommended. For best results, use at room temperature. Cover adjacent areas to protect from overspray.

Shake can vigorously for one minute after mixing ball begins to rattle and often during use. Hold can upright, moving from side-to-side while spraying lightly and evenly about 30 cm (12") from area being painted. Two to three thin coats produce best results.

CLEAN-UP & DISPOSAL

Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean. Do not stick pins or wire into can opening. Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

Visit behr.ca for painting tips, project advice and colour coordination with the ColourSmart by BEHR™ Tool, or download the ColourSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Health Canada at 1-866-225-0709 or log on to www.canada.ca/en/health-canada/services/home-safety/lead-based-paint.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** Some provinces do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from province to province. To obtain warranty service, call 1-800-661-1591. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company representative, call 1-800-661-1591.

EXTREME DANGER! VERY FLAMMABLE, POISON, IRRITANT, CONTENTS UNDER PRESSURE. CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. FUMES HARMFUL. MAY IRRITATE EYES AND SKIN. CONTAINER MAY EXPLODE WHEN HEATED. Do not smoke. Do not swallow. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Do not puncture. Do not burn. Use only with adequate ventilation. Wear a mask/ respirator while handling the product. Keep away from flames, such as pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear eye protection and protective clothing. Store away from heat. **FIRST AID TREATMENT:** May contain: ACETONE; BUTYL ACETATE; PROPANE; TITANIUM DIOXIDE; ISOBUTANE; GROUND CALCIUM CARBONATE; 1-METHOXY-2-PROPYL ACETATE; METHYL ETHYL KETONE; STODDARD SOLVENT; CARBON BLACK; 3-ETHOXYPROPIONIC ACID ETHYL ESTER; SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; SILICON DIOXIDE; AND NAPHTHA (PETROLEUM), HYDROTREATED HEAVY. If swallowed, call Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 15 – 20 minutes. If on skin rinse with water. If inhaled move person to fresh air.

