



BEHR® Interior/Exterior Multi-Surface Stain-Blocking Primer & Sealer

No. 436 White

- Excellent Adhesion Helps Resist Peeling
- Alkali and Efflorescence Resistant
- Blocks Medium to Heavy Stains
- High-Hide White
- Quick Recoat Time
- Low VOC
- Mildew Resistant Finish
- Tintable up to 118 mL of Colourant per 3.78L



30 Min Dries to Touch
1 Hr Ready to Topcoat



23 - 37 m² Coverage
per 3.78L



Soap & Water
Clean-Up



Protect
from Freezing

WHERE TO USE

Over properly prepared uncoated and previously painted Interior/Exterior surfaces. Ideal for Masonry, Stucco, Drywall, Galvanized Metal, Ferrous Metals, Vinyl, Aluminum, Wood, Concrete and on glossy surfaces or oil-based paint.

PREPARATION

All surfaces should be properly prepared and cleaned. Remove loose paint, wash off chalk, dirt, and grease with detergent, rinse and allow to dry. Remove mildew stains with a mildew stain removing product. Scuff sand glossy and metal surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. Allow new masonry stucco, concrete, concrete masonry units (CMUs), and split-faced block to cure for 7 days and test pH prior to applying primer. The pH must be 13.0 or lower before coating. Remove efflorescence with a mixed solution of one part vinegar and one part water, rinse thoroughly with clean water and allow to dry. **FOR EXTERIOR SURFACES:** For new or uncoated wood, use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. Etch galvanized metal with a product such as BEHR PREMIUM Concrete & Masonry Cleaner & Etcher No. 991.

APPLICATION

Apply when air and surface temperatures are between 2 – 32° C. Use a high quality 10 – 13 mm nap roller cover, nylon/polyester brush or an airless sprayer (.015 – .021" spray tip, 60 mesh filter). Stir primer occasionally. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 237 ml per 3.78 L. Spot prime patched areas first, then follow with a complete primer coat. Two coats may be needed over heavy stains and tannin-rich wood. On stained surfaces, topcoat in 4 hours; for heavy stains, topcoat in 16 hours. Topcoat within 30 days. Bright or deep colours require a tinted primer. Have primer tinted close to topcoat colour with no more than 118 mL of colourant per 3.78 L.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect colour coordination with the ColourSmart by BEHR™ Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Health Canada at 1-866-225-0709 or log on to www.canada.ca/en/health-canada/services/home-safety/lead-based-paint.

LIFETIME LIMITED WARRANTY Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A 2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-661-1591.



MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Keep out of reach of children. Wear eye protection and protective clothing. Use only with adequate ventilation. Keep out of reach of children. Keep away from flames or sparks. **FIRST AID TREATMENT:** Contains NEPHELINE SYENITE, TITANIUM DIOXIDE AND ETHYLENE GLYCOL. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

