



BEHR PREMIUM Granite Grip™

No. 650 Gray

No. 655 Tan

- Resists Hot Tire Pick-Up
- Available in Custom Colors
- Durable, Textured Finish
- Fills in Hairline Cracks
- Resists Household Stains



Spread Rate:
Rough 40-50 Sq. Ft.
Smooth 50-60 Sq. Ft.



2 Coats
Required



Dry Time:
1 Hr. Dry to Touch
3-4 Hr. Recoat



Protect:
from Freezing

IMPORTANT! DO NOT OPEN CONTAINER WITHOUT READING INSTRUCTIONS. 2 COATS REQUIRED. USE WITH 1/4" ADHESIVE ROLLER COVER.

WHERE TO USE

On Interior/Exterior surfaces such as: Garage Floors, Driveways, Basement Floors, Porches and Pool Decks.

WHERE NOT TO USE

DO NOT use on vertical surfaces or areas subject to hydrostatic pressure. NOT for industrial use or areas subject to forklifts.

PREPARATION* (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease.
- **New and Uncoated Concrete or Masonry Surfaces:**
- Allow new surfaces to cure 30 days.
- Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper.

Wipe your fingers over the clean, dry floor to check for dust or powder. Ensure there is no residue on your fingers that may have been left from the etcher. If residue is found, rinse the surface to remove residue. Allow the surface to dry completely. Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.

Painted, Stained or Sealed Concrete:

- For a painted surface in sound condition, use a product to clean and prepare the surface.
- If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface.
- Scuff sand glossy surfaces.
- Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

APPLICATION

- **DO NOT THIN.** Intermix all cans of same product to ensure color uniformity.
- Stir before and occasionally during application.
- Use product when air and surface temperatures are between 50-90° F.
- Apply to dry concrete. Do not apply if rain or heavy dew is expected within 24 hours.
- Do not apply in direct sunlight.
- For hairline cracks up to 1/8", completely fill in with coating using a nylon/polyester brush and allow to dry completely prior to roller application.
- For best results, do not pour product directly on surface; always use a roller tray.
- Apply a thin first coat using a 1/4" adhesive roller cover or nylon/polyester brush.
- **NOTE:** The first coat will act as the base coat and it will not completely cover the surface by design. Avoid over application on the first coat.
- Apply in 4' x 4' sections. Begin with the roller in the center of the section and roll outwards in random directions.

- Avoid regular patterns and knock down hard edges using the roller.
- Allow first coat to dry then apply second coat in the same method as the first coat.
- While two coats are necessary, additional coats may help hide previous surface imperfections or cover over dark colors.
- For large projects, consider using a texture sprayer with a 4mm tip.
- Spray in 4' x 4' sections and back roll with an adhesive roller cover.
- Soap & water clean-up. An annual touch-up may be required in areas subject to tire traffic.

DRY TIME

- Longer dry time required in cooler temperatures and in higher humidity.
- The floor may be subjected to light foot traffic after 24 hours.
- Allow 72 hours before subjecting surface to automotive tires, heavy foot traffic or repositioning furniture.
- Premature heavy traffic will cause paint failure requiring spot recoating.
- Wait at least 30 days before rinsing or cleaning. Use a mild detergent as needed.
- Abrasive cleaners and pressure-washers should be used carefully to avoid premature coating failure.

DISPOSAL

- Properly dispose of all soiled rags.
- To recycle or properly dispose of product in your community, contact your household refuse collection service.

LIMITED WARRANTY

Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Cancer and Reproductive Harm www.P65Warnings.ca.gov

CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 03/18